

Material Safety Data Sheet

1. Product and Company Identification

Product Name: Cutek CD50 LVOC Wood Preservative
Trade Name: Special CutekCD50 LOW VOC Version
Revision Date: 2/2/2010
Company Name: Chemisys Australia Pty Ltd
A.C.N. 096 578 013
Address: P. O. Box 3604
Loganholme
QLD 4129
Australia
Phone 0438 923248 Fax 07 32877288

Hazardous according to the criteria of Worksafe Australia
Not classified as hazardous for transport (ADG, UN, IATA/ICAO)

2. Composition/Information on Ingredients

Ingredients considered hazardous according to the criteria of Worksafe Australia:

Chemical Name	CAS #	Proportion	EU Classification
Heavy Aromatic Petroleum Solvent	[64742-94-5]	10-<30%	Xn; R65
Phosphoric Esters	[12645-31-7]	<10%	Xi; R36, R38
Copper-8-Hydroxyquinoline	[10380-28-6]	<10%	R52

Ingredients determined not to be hazardous to 100%

VOC Content 173 gms/litre.

VOC Test Method: ASTM D3960 Standard Practice for Determining Volatile Organic Compound (VOC) Content of Paints and Related Coatings. Note: These figures only apply to Special Low VOC Version of Cutek CD50 LVOC which is appropriately labelled as such.

Notes on EU Symbols: Xn Harmful, Xi Irritant

3. Hazards Identification

Harmful: Low viscosity material may cause lung damage if swallowed.

Irritating to eyes and skin.

Harmful to aquatic organisms. This product is technically toxic to aquatic organisms because of its copper content; however in this form it has negligible solubility in water so is unlikely to pose a significant risk.

4. First Aid Measures

Eyes:

Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids apart to ensure flushing of the entire eye surface. Seek medical attention as soon as possible.

Ingestion:

DO NOT induce vomiting. If vomiting occurs spontaneously, keep airway clear. Seek medical attention IMMEDIATELY. NEVER induce vomiting or give anything by mouth to an unconscious patient.

Inhalation:

Remove victim to fresh air. Persons administering first aid to overexposure victims should carefully wash off any visible product from the victims face. Do not give anything by mouth to an unconscious person. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult administer oxygen. Get medical attention IMMEDIATELY.

Skin:

Wash with plenty of soap and water. Remove contaminated clothing and footwear. Wash clothing and contaminated footwear before reuse. Seek medical attention if irritation persists.

Note to doctor:

Treat symptomatically. Aspiration of material into lungs due to vomiting may cause chemical pneumonitis.

5. Fire-Fighting Measures

Flash Point:	92 degrees Celsius (ASTM D92)
Extinguisher Media:	Foam, carbon dioxide, dry chemical.
Unusual Fire and Explosion Hazards:	None known
Special Protective Equipment:	Fires in confined spaces should be dealt with by trained personnel wearing approved breathing apparatus.
Combustion Products:	Toxic fumes may be evolved on burning or exposure to heat. (See Section 10 of this MSDS)

6. Accidental Release Measures

Hazards:

This product is technically toxic to aquatic organisms because of its copper content; however in this form it has negligible solubility in water so is unlikely to pose a significant risk. Do not contaminate waterways.

Steps to be taken if material is released or spilled:

Wear appropriate protective clothing. Eliminate all ignition sources. Restrict access to contaminated area. Stop spill at source. Dike to prevent spreading. Collect free liquid into a recovery vessel. Absorb remainder with sand or clay and place in a properly labelled waste receptacle. Follow all government and local body regulations for disposal. Do not contaminate water while cleaning equipment or disposing of wastes. Prohibit contamination of streams, lakes and other bodies of water.

Container Disposal:

DO NOT reuse container. Dispose of safely.

7. Handling and Storage

Handling:

Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practises. Wash hands thoroughly after contact.

Storage:

Store in a cool, dry place out of reach of children.
Incompatible with unlined metal containers.

8. Exposure Controls/Personal Protection

Ventilation Requirements:

Ventilate via mechanical methods (general or local exhaust) to maintain exposure below 5mg/m³. Good industrial hygiene practise dictates that indoor work areas should be isolated and provided with adequate local exhaust ventilation.

Respiratory Protection:

None normally required if good ventilation is maintained. If mist is generated during application process, use a disposable mist respirator. Avoid breathing vapour

Eye Protection:

If accidental eye contact is possible then wear goggles or a face visor.

Skin Protection:

Unnecessary skin contact should be avoided and good personal hygiene practises observed. If skin contact is anticipated then protective clothing including impervious gloves should be worn.

9. Physical and Chemical Properties

Appearance:	Dark green/amber liquid.
Odour:	Slight petroleum distillate odour.
PH Range:	2.8 – 3.8
Specific Gravity:	0.90 @ 20 degrees Celsius
Solubility in Water:	Negligible
Flash Point:	92 degrees Celsius (ASTM D92)
VOC Content:	173 grams/litre
VOC Test Method:	ASTM D3960 Standard Practice for Determining Volatile Organic Compound (VOC) Content of Paints and Related Coatings.

10. Stability and Reactivity

Stability: Products of this type are stable and unlikely to react in a hazardous manner under normal conditions.

Incompatibility: Strong Oxidising Agents

Hazardous Decomposition Products: Oxides of Carbon.

Hazardous Polymerisation: Will not occur

9. Toxicological Data

Eyes:

Not available. Can cause severe irritation, redness, tearing, and blurred vision. Can cause irreversible damage on prolonged contact.

Ingestion:

Not available. Can cause gastro-intestinal irritation, nausea, vomiting, and diarrhoea.

Inhalation:

Not available. At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. Can cause nasal and respiratory irritation, dizziness, nausea, vomiting, headache, and weakness.

Skin:

Not available. Prolonged or repeated contact may result in itching, defatting, dermatitis or more serious irreversible skin disorders.

12. Ecological Information

Hazard:

This product is technically toxic to aquatic organisms because of its copper content; however in this form it has negligible solubility in water so is unlikely to pose a significant risk. Do not contaminate waterways.

Mobility:

Spillages may penetrate the soil however the product is also insoluble in water so is unlikely to pose a significant risk to the environment.

13. Disposal Considerations

Dispose of via an authorised person/licensed waste disposal contractor in accordance with local regulations.

Incineration may be carried out under controlled conditions provided that local regulations for emissions are met.

Dispose of product and container responsibly and carefully.

Do not dispose of near waterways, down drains or into soil.

14. Transport Information

Not classified as hazardous for transport (ADG, UN, IATA/ICAO)

Classified as a Combustible Liquid C1, AS 1940-1993

15. Regulatory Information

Australian Classifications:

UN Number:	NA
HAZCHEM Code:	NA
Dangerous Goods Class	NA
Packaging Group:	NA
EC Labelling:	Xn; R65, Xi; R36/R38, R52

S2, S23, S24, S25, S62

16. Other Information

Compiled by:

Chemisys Australia Pty Ltd
A.C.N. 096 578 013

P. O. Box 3604
Loganholme
QLD 4129
Australia

This data sheet and the health, safety and environmental information it contains is considered to be accurate as of the date specified. However no warranty or representation, expressed or implied is made as to the accuracy or completeness of the data and the information in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Chemisys Group shall not be responsible for any damage of injury resulting from abnormal use of this material, from any failure to adhere to recommendations or from any hazards inherent in the nature of the material.