

## FEATURES

Biodegradable cleaner  
Rapid removal of grease and grime from all hard surfaces

## USES

Quickclean is an industrial grade general purpose cleaner for use on dirty wood and other substrates such as factory floors & barbeques.  
Always patch test Quickclean before use.

## SPECIFICATIONS

### TYPICAL PROPERTIES AND APPLICATION DATA

|                |  |
|----------------|--|
| CLASSIFICATION | Industrial grade general purpose cleaner/degreaser                           |
| COMPONENTS     | One  |
| FLASH POINT    | NA   |
| PH             | ~10.8 as supplied  |
| THINNER        | May be thinned with water up to 1:100 V/V recommended start point is 1:8 V/V |
| PACK SIZES     | 2.5L, 5L, 20L, 200L, 1000L   |
| PRODUCT CODE   | D390   |

### SPREADING RATE

NOTE: Practical spreading rates will vary depending on such factors as application method, ambient conditions and surface porosity and roughness.

ALL SURFACES Vaies according to dilution

### SUBSTRATE

This is a guide only and not to be used as a specification. Your specific project needs must be discussed with a CUTEK® consultant

| SURFACE  | ENVIRONMENT | PREPARATION GUIDE   | SYSTEM               | COLOUR TONE ADDED (Y/N) |
|--|-------------|---|----------------------|-------------------------|
| WOOD – OLD<br>PREVIOUSLY COATED<br>WITH CUTEK® | EXTERIOR    | Clean with Proclean if<br>tannin/water/iron stained<br><br>Otherwise clean with<br>Quickclean | 1st Coat: CUTEK® Oil | Y                       |

## APPLICATION

### APPLICATION PRECAUTIONS

Full list of application precautions is available on website at [www.cutek.com.au](http://www.cutek.com.au), or by checking with customer services on 1300 128835.

### BEFORE YOU GET STARTED

Before you begin, note the hazards and precautions on this website and the can labelling, and ensure that you use the correct safety equipment as detailed in the Safety Data Sheet.

### STEP BY STEP APPLICATION PROCESS

Unlike bleach, CUTEK® Quickclean is not considered a strong defoliant, however, we recommend using absorbent drop cloths to protect delicate and/or adjacent vegetation and surfaces.

CUTEK® Quickclean must be diluted 8:1 with water. Always test to determine if the dilution being used is effective in cleaning. If the timber is proving difficult to clean, it might be more cost effective to use CUTEK® Proclean instead of CUTEK® Quickclean on a large project.

Before you begin, note the hazards and precautions on this website and the can labelling, and ensure that you use the correct safety equipment as detailed in the Safety Data Sheet.

After testing a patch of timber, apply CUTEK® QuickClean liberally to the timber substrate with brush, roller, or garden sprayer. Let CUTEK® QuickClean do most of the work by letting it sit on the surface for 10 – 20 minutes, or such time as deemed to be necessary by the test procedure. It may be necessary to scrub stubborn stains moderately with a stiff fibre brush.

Once CUTEK® Quickclean has cleaned the timber, it must be power rinsed off thoroughly. For best results, power rinse with a high-pressure washer set to under 750 p.s.i. (50 bar), with a fan jet pattern to avoid damage to the wood fibre.

Clean from the highest point and work down methodically. ALWAYS clean off with a water jet that produces a "putty knife" shaped fan that is 40–50mm wide about 100mm out from jet. Adopt a continuous "mowing action" working with power water fan-jet 100mm from the face of the substrate. DO NOT use "turbojets" on timber.

CAUTION must be used when cleaning soft timber to reduce the pressure and avoid damaging the sapwood. The longer that CUTEK® QuickClean is left on the substrate, the greater the rinse time required. Additionally, certain types of wood surfaces may leave a raised grain effect after stripping is completed. Sanding or poly pad scrubbing may be required to smooth out this condition.

Following the restoration of the timber with CUTEK® Quickclean, it is important to complete the restoration process by coating the timber with an appropriate CUTEK® oil, following the procedure detailed in this website.

Not treating the timber after cleaning will result in the weathering process occurring more rapidly than prior to cleaning.

### CLEANUP

Equipment may be cleaned with soap and water. All wash water is to be disposed of properly.

## STORAGE & SAFETY

**SAFETY** Read Data Sheet, SAFETY DATA SHEET and any precautions on container labels and SAFETY DATA SHEET.

**STORAGE** This product NOT classified as dangerous goods for transport or storage in Australia. Store in well ventilated bunded area under cover and away from sources of heat. Keep containers closed at all times.

**HANDLING** As with any chemical, ingestion, inhalation or contact with eyes and skin should be avoided by good occupational work practice. Eye protection approved to AS1337 and skin protection approved to AS2161 should be worn where there is a risk of splashes entering the eyes or contacting the skin. Always wash hands before smoking, eating, drinking or using the toilet.

**USING** Use with good ventilation and avoid inhalation of spray mists and fumes. If risk of inhalation of spray mists exists, wear combined organic vapour/particulate respirator.

**FLAMMABILITY** This product is not flammable. On burning will emit toxic fumes.

## COMPANY INFORMATION

**Chemisys Cutek Pty Ltd**

**A.C.N. 610 127 654**

**P. O. Box 3604**

**Loganholme QLD 4129**

**Australia**

The data presented in this medium and any advice, recommendation, information, assistance or service provided by Chemisys relation to goods manufactured by it or their use and application is given in good faith and is believed by Chemisys to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Chemisys does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from determining suitability of the product their own purpose. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.