

SAFETY DATA SHEET

1. Identification

Product identifier CUTEK® Machine Coat

Other means of identification Not available.

Recommended use Industrial pre-treatment for timber

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Distributor

Telephone

Company nameCUTEK America LLCDeck Source Inc.Address6810 Tordera St22 Winstar Rd, Unit 1Coral Gables, FLOro-Mednote, ON33146 USAL0L 2E0 Canada

1-833-MY-CUTEK (1-833-692-8835)

E-mail Not available.

Emergency phone number EMERGENCY CONTACT: 1-855-237-5573

POISON CONTROL HOTLINE: 1-800-222-1222

2. Hazard identification

Physical hazardsFlammable liquidsCategory 4Health hazardsSensitization, skinCategory 1Specific target organ toxicity, repeatedCategory 1

exposure

Aspiration hazard

Environmental hazards Not classified.

WHMIS 2015 defined hazards Not classified

Label elements



Signal word Danger

Hazard statement Combustible liquid. May cause an allergic skin reaction. Causes damage to organs through

prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear

Category 1

protective gloves, protective clothing, eye protection and face protection.

Response In case of fire: Use carbon dioxide, dry chemical, water spray, or foam to extinguish.

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention.

Take off contaminated clothing and wash it before reuse.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

Get medical attention if you feel unwell.

Storage Store in a well-ventilated place. Store locked up.

Disposal Dispose of container in accordance with local, regional, national and international regulations.

WHMIS 2015: Health Hazard(s)

not otherwise classified

WHMIS 2015: Physical

(HHNOC)

None known

Hazard(s) not otherwise classified (PHNOC)

Hazard(s) not otherwise

classified (HNOC)

None known.

None known

Supplemental information None.

#34136 Page: 1 of 8 Issue date 28-October-2021

3. Composition/Information on ingredients **Mixture Chemical name CAS** number % Common name and synonyms 1 - 5 * Alkyl (C12-14) glycidyl ether 68609-97-2 Butylcarbamic acid, 55406-53-6 0.1 - 1 * 3-iodo-2-propynyl ester Distillates (petroleum), hydrotreated 64742-55-8 60 - 80 * light paraffinic Naphtha (petroleum), hydrotreated 64742-48-9 10 - 30 * heavy All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. US GHS: The exact percentage (concentration) of composition has been withheld as a trade **Composition comments**

secret in accordance with paragraph (i) of §1910.1200.

*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

Skin contact

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

Eye contact

Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical

attention if irritation persists.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation. May cause an allergic skin reaction. Dermatitis. Rash.

Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Treat patient symptomatically.

General information

If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Hazardous combustion

Combustible liquid. May include and are not limited to: Oxides of carbon.

products

media

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not breathe mist or vapor. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

#34136 Page: 2 of 8 Issue date 28-October-2021

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Observe good industrial hygiene practices. Wash thoroughly after handling. When using, do not eat, drink or smoke.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children. Store locked up.

8. Exposure controls/Personal protection					
upational exposure limits					
Canada. Alberta OELs (Occupation	•		_		
Components	Туре	Value	Form		
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.		
	TWA	5 mg/m3	Mist.		
Canada. Manitoba OELs (Reg. 217	/2006, The Workplace Safety A	nd Health Act)			
Components	Туре	Value	Form		
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.		
Canada. Ontario OELs. (Control of Components	· ·	mical Agents) Value	Form		
•	Type				
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.		
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	525 mg/m3			
Canada. Quebec OELs. (Ministry o	f Labor - Regulation respecting	g occupational health and s	afety)		
Components	Туре	Value	Form		
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.		
(CAS 64742-55-8)					
(CAS 64742-55-8)	TWA	5 mg/m3	Mist.		
Canada. Saskatchewan OELs (Occ	cupational Health and Safety Re	egulations, 1996, Table 21)	Mist.		
Canada. Saskatchewan OELs (Occ Components	cupational Health and Safety Re	egulations, 1996, Table 21) Value	Mist.		
Canada. Saskatchewan OELs (Occ Components Distillates (petroleum), hydrotreated light paraffinic	cupational Health and Safety Re	egulations, 1996, Table 21)	Mist.		
Canada. Saskatchewan OELs (Occ Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	cupational Health and Safety Re	egulations, 1996, Table 21) Value	Mist.		
Canada. Saskatchewan OELs (Occ Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	cupational Health and Safety Re Type 15 minute 8 hour	egulations, 1996, Table 21) Value 10 mg/m3 5 mg/m3	Mist.		
Canada. Saskatchewan OELs (Occ Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. OSHA Table Z-1 Limits for Air	cupational Health and Safety Re Type 15 minute 8 hour	egulations, 1996, Table 21) Value 10 mg/m3 5 mg/m3	Mist.		
Canada. Saskatchewan OELs (Occ Components Distillates (petroleum), hydrotreated light paraffinic	cupational Health and Safety Re Type 15 minute 8 hour Contaminants (29 CFR 1910.10	egulations, 1996, Table 21) Value 10 mg/m3 5 mg/m3			
Canada. Saskatchewan OELs (Occ Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. OSHA Table Z-1 Limits for Air Components Distillates (petroleum), hydrotreated light paraffinic	supational Health and Safety Re Type 15 minute 8 hour Contaminants (29 CFR 1910.10 Type PEL	10 mg/m3 5 mg/m3 Value Value	Form		
Canada. Saskatchewan OELs (Occ Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. OSHA Table Z-1 Limits for Air Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. ACGIH Threshold Limit Values	supational Health and Safety Re Type 15 minute 8 hour Contaminants (29 CFR 1910.10 Type PEL	10 mg/m3 5 mg/m3 Value Value	Form		
Canada. Saskatchewan OELs (Occ Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. OSHA Table Z-1 Limits for Air Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	supational Health and Safety Re Type 15 minute 8 hour Contaminants (29 CFR 1910.10 Type PEL	999, Table 21) Value 10 mg/m3 5 mg/m3 900) Value 5 mg/m3	Form Mist.		
Canada. Saskatchewan OELs (Occ Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. OSHA Table Z-1 Limits for Air Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. ACGIH Threshold Limit Values Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. NIOSH: Pocket Guide to Chem	supational Health and Safety Re Type 15 minute 8 hour Contaminants (29 CFR 1910.10 Type PEL Type TWA	999, Table 21) Value 10 mg/m3 5 mg/m3 900) Value 5 mg/m3 Value 5 mg/m3	Form Mist. Form Inhalable fraction.		
Canada. Saskatchewan OELs (Occ Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. OSHA Table Z-1 Limits for Air Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. ACGIH Threshold Limit Values Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. NIOSH: Pocket Guide to Chem Components	Eupational Health and Safety Re Type 15 minute 8 hour Contaminants (29 CFR 1910.10 Type PEL Type TWA ical Hazards Type	segulations, 1996, Table 21) Value 10 mg/m3 5 mg/m3 1000) Value 5 mg/m3 Value 5 mg/m3 Value 5 mg/m3	Form Mist. Form Inhalable fraction. Form		
Canada. Saskatchewan OELs (Occ Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. OSHA Table Z-1 Limits for Air Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) US. ACGIH Threshold Limit Values Components Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	supational Health and Safety Re Type 15 minute 8 hour Contaminants (29 CFR 1910.10 Type PEL Type TWA	999, Table 21) Value 10 mg/m3 5 mg/m3 900) Value 5 mg/m3 Value 5 mg/m3	Form Mist. Form Inhalable fraction.		

#34136 Page: 3 of 8 Issue date 28-October-2021

No biological exposure limits noted for the ingredient(s). **Biological limit values**

Appropriate engineering

controls

Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields.

Skin protection

Wear appropriate chemical resistant gloves. Confirm with a reputable supplier first. Hand protection

Other As required by employer code.

Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134),

CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards Not applicable.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks

and immediately after handling the product. When using, do not eat, drink or smoke.

9. Physical and chemical properties

Appearance Liquid Physical state Liquid. Liquid. **Form** Not available. Color Odor Not available. Not available. Odor threshold Not available. pН Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

Pour point Not available. 0.84 @ 21°C Specific gravity Partition coefficient Not available.

(n-octanol/water)

Flash point 154.4 °F (68.0 °C) ASTM D93

Evaporation rate Not available. Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

18 cSt @ 40°C

(%)

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. Not available. Vapor pressure Not available. Vapor density Not available. Relative density Not available. Solubility(ies) Not available. **Auto-ignition temperature** Not available. **Decomposition temperature**

Other information

Viscosity

Explosive properties Not explosive. Oxidizing properties Not oxidizing.

VOC 250 g/I ASTM D2369

10. Stability and reactivity

Reactivity May react with incompatible materials.

#34136 Page: 4 of 8 Issue date 28-October-2021 Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Chemical stability

Material is stable under normal conditions.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not mix

with other chemicals.

Strong oxidizing agents.

Incompatible materials

Hazardous decomposition

products

May include and are not limited to: Oxides of carbon.

11. Toxicological information

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia. May cause stomach distress, nausea or vomiting.

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause an allergic skin reaction.

Dermatitis, Rash.

Information on toxicological effects

Acute toxicity Not classified.

Components Species Test Results

Alkyl (C12-14) glycidyl ether (CAS 68609-97-2)

Acute

Dermal

LD50 Rat 4000 mg/kg, ECHA

Inhalation

LC50 Rat 0.2 mg/L, 7 h, ECHA

Oral

LD50 Rat > 2000 mg/kg, ECHA

30.1 ml/kg, ECHA

Butylcarbamic acid, 3-iodo-2-propynyl ester (CAS 55406-53-6)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg, HSDB

Inhalation

LC50 Not available

Oral

LD50 Rat 1500 mg/kg, HSDB

1100 mg/kg, HSDB

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg, ECHA

Inhalation

LC50 Rat > 5.5 mg/L, 4 Hours, ECHA

Oral

LD50 Rat > 5000 mg/kg, ECHA

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Acute

Dermal

LD50 Rabbit > 1900 mg/kg, 24 Hours, ECHA

Inhalation

LC50 Rat > 5 mg/L, 4 Hours, ECHA

#34136 Page: 5 of 8 Issue date 28-October-2021

Components Species Test Results

Oral

LD50 Rat > 5000 mg/kg, ECHA

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Exposure minutes Not available.

Erythema value Not available.

Oedema value Not available.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Corneal opacity value Not available.

Iris lesion value Not available.

Conjunctival reddening Not available.

value

Conjunctival oedema value Not available.

Recover days Not available.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Contains < 3% (w/w) DMSO-extract

ACGIH Carcinogens

Distillates (petroleum), hydrotreated light paraffinic (CAS A2 Suspected human carcinogen.

64742-55-8)

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Naphthalene (CAS 91-20-3)

Canada - Manitoba OELs: carcinogenicity

Distillates (petroleum), hydrotreated light paraffinic (CAS Suspected human carcinogen.

64742-55-8)

IARC Monographs. Overall Evaluation of Carcinogenicity

Naphtha (petroleum), hydrotreated heavy (CAS Volume 47 - 3 Not classifiable as to carcinogenicity to humans.

64742-48-9)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

US NTP Report on Carcinogens: Known carcinogen

Distillates (petroleum), hydrotreated light paraffinic (CAS Known To Be Human Carcinogen.

64742-55-8)

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Teratogenicity Not available.

Specific target organ toxicity - Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity See below

Ecotoxicological data

Components Species Test Results

Butylcarbamic acid, 3-iodo-2-propynyl ester (CAS 55406-53-6)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 0.05 - 0.089 mg/L, 96 hours

(Oncorhynchus mykiss)

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

Crustacea EC50 Daphnia 1000 mg/L, 48 Hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soilNo data available.Mobility in generalNot available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Empty containers or liners may retain some product residues. This material and its container must

be disposed of in a safe manner (see: Disposal instructions).

Contaminated packagingSince emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the

product will appear below.

U.S. Department of Transportation (DOT)

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory information

Canadian federal regulationsThis product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Naphtha (petroleum), hydrotreated heavy (CAS 1 TONNES

64742-48-9)

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not applicable

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely

hazardous substance

No

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

categories Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#34136 Page: 7 of 8 Issue date 28-October-2021

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

US - California Hazardous Substances (Director's): Listed substance

Distillates (petroleum), hydrotreated light paraffinic Listed

See below

(CAS 64742-55-8)

US - Minnesota Haz Subs: Listed substance

Distillates (petroleum), hydrotreated light paraffinic Listed.

(CAS 64742-55-8)

US - Texas Effects Screening Levels: Listed substance

Butylcarbamic acid, 3-iodo-2-propynyl ester (CAS Listed.

55406-53-6)

Distillates (petroleum), hydrotreated light paraffinic Listed.

(CAS 64742-55-8)

Naphtha (petroleum), hydrotreated heavy (CAS Listed.

64742-48-9)

US. Massachusetts RTK - Substance List

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

US. New Jersey Worker and Community Right-to-Know Act

Butylcarbamic acid, 3-iodo-2-propynyl ester (CAS 55406-53-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

US. Rhode Island RTK

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

US. California Proposition 65



WARNING: This product can expose you to chemicals including Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Naphthalene (CAS 91-20-3) Listed: April 19, 2002

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information







Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 28-October-2021

Version # 01

Effective date 28-October-2021

Prepared by Dell Tech Laboratories Ltd. Phone: (519) 858-5021

Further information Not available.

Other information For an updated SDS, please contact the supplier/manufacturer listed on the first page of the

document.