

CUTEK® QUICKCLEAN

GENERAL PURPOSE OUTDOOR CLEANER CONCENTRATE



BENEFITS

- **Powerful outdoor cleaner** – general-purpose cleaner that removes dirt, grease and grime from outdoor surfaces
- **Perfect for regular wood cleaning** – prepares wood for a maintenance coat of CUTEK® Extreme
- **Clean up CUTEK® spills with ease** – easily cleans accidental spills of CUTEK® Extreme
- **Cleans all hard surfaces** – including composite decking, plastic, PVC, tiles, pavers, concrete and glass.

USES

CUTEK® Quickclean is a powerful general-purpose outdoor cleaner that removes dirt grease and grime from all your exterior hard surfaces.

It will easily remove dirt, grease, and grime as well as even out CUTEK® Colourtone that has started to wear or erode unevenly on your wood.

It is the perfect way to regularly keep all your wood clean, and it prepares wood to optimize the performance of maintenance coats of CUTEK® Extreme.

CUTEK® Quickclean is a concentrate that should be diluted with water. The dilution will vary depending on the build-up of dirt/grease on the surface.

SPECIFICATIONS

TYPICAL PROPERTIES AND APPLICATION DATA

CLASSIFICATION	Industrial grade general purpose cleaner/degreaser
COMPONENTS	One
FLASH POINT	NA
pH	~13 as supplied
THINNER	May be thinned with water up to 1:100 V/V recommended start point is 1:8 V/V
PACK SIZES	1.89L (64 oz.)



COVERAGE RATE

All surfaces: 4-7 m²/L (160-285 ft²/gal)

DILUTION & COVERAGE GUIDE

	DILUTION	MIXED VOL.	COVERAGE
To remove oil and fat based stains	Full strength	1.89 L / 64 oz	Spot cleaning
Wood and composite decking, wood shingles	1:8	17 L / 4.5 gal	79 m ² / 850 ft ²
PVC and capped composite decking	1:20	39.7 L / 10.5 gal	186 m ² / 2000 ft ²
Plastic / PVC / ceramic tiles / canvas / metal	1:50	96.4 L / 25.5 gal	446 m ² / 4800 ft ²
All purpose glass cleaner	1:100	190.9 L / 50.5 gal	883 m ² / 9500 ft ²

NOTE: Coverage rates represent typical averages, and will vary depending on factors such as application method, ambient conditions, and surface porosity roughness. This chart is to be used as a guideline only.



PREPARATION AND PROTECTION GUIDELINE

This is a guide only and not to be used as a specification. Contact CUTEK® to discuss your specific project requirements.

WOOD CONDITION/ DESIRED EFFECT	SITUATION	PREPARATION	PROTECTION	ADD CUTEK® COLOURTONE? (Y/N)
NEW Wood Retain freshly oiled look or alter the wood colour	Exterior	Clean with CUTEK® Wood Reviver if tannin/water/iron stained Otherwise clean with CUTEK® Quickclean	Apply 2 coats of CUTEK® Extreme	Y
NEW Wood Stabilize & allow to naturally lighten/silver	Exterior	Clean with CUTEK® Wood Reviver if tannin/water/iron stained otherwise clean with CUTEK® Quickclean	Apply 2 coats of CUTEK® Extreme	N
OLD WOOD - Previously Coated in CUTEK® Extreme Retain freshly oiled look or alter the wood colour	Exterior	Clean with CUTEK® Wood Reviver if maintenance has been neglected and wood is grayed, heavily stained or has an excessive build-up of CUTEK® Colourtone. Otherwise clean with CUTEK® Quickclean.	Apply 1 coat of CUTEK® Extreme	Y
OLD WOOD - Previously Coated in CUTEK® Extreme Stabilize & allow to naturally lighten/silver	Exterior	Prepare for maintenance by cleaning with CUTEK® Quickclean. Clean with CUTEK® Wood Reviver if maintenance has been neglected and wood is heavily stained or you would like to revive the original colour.	Apply 1 coat of CUTEK® Extreme	N
OLD WOOD - Previously uncoated Retain freshly oiled look or alter the wood colour	Exterior	Clean with CUTEK® Wood Reviver if tannin/water/iron stained otherwise clean with CUTEK® Quickclean	Apply 2 coats of CUTEK® Extreme	Y
OLD WOOD - Previously uncoated Stabilize & allow to naturally lighten/silver	Exterior	Clean with CUTEK® Wood Reviver if tannin/water/iron stained otherwise clean with CUTEK® Quickclean	Apply 2 coats of CUTEK® Extreme	N



DIRECTIONS FOR USE

APPLICATION

APPLICATION PRECAUTIONS

Before you get started: Note the hazards and precautions on the CUTEK® website and the container labelling, and ensure that you use the correct safety equipment as detailed in the Safety Data Sheet.

When using CUTEK® Quickclean, all adjacent surfaces and vegetation must be adequately protected. It is also important to be aware of the potential for wind drift into areas with cars or pedestrian traffic when rinsing. Water flush all equipment, vegetation, paths, concrete, asphalt and other adjacent surfaces before and after contact.

Full list of application precautions is available on our website at www.cutekstain.com, or by checking with customer service on 1-844-442-8835.

DO NOT SWALLOW.

CUTEK® Quickclean will make surfaces slippery, DO NOT walk on the surface until it is dry.

STEP BY STEP APPLICATION PROCESS

Dilute the CUTEK® Quickclean concentrate with water as required and complete a test patch to ensure that the dilution being used is effective in cleaning. Wet your substrate with water prior to applying CUTEK® Quickclean. Apply diluted CUTEK® Quickclean liberally with a brush, roller, broom or low-pressure garden sprayer. Let CUTEK® Quickclean do the work by leaving it on the surface for 5 to 15 minutes depending on the severity of dirt/soiling/grease. It may be necessary to scrub stubborn stains moderately with a stiff fibre brush.

Once CUTEK® Quickclean has cleaned the substrate, it must be rinsed off thoroughly. For best results, use a pressure washer set to approximately 50 bar (750 p.s.i.) with a fan jet pattern. Keep an operating distance of at least 4" from the wood. CAUTION must be used to avoid damage to the wood fiber and 'furring up'. Adjust your cleaning process by reducing the pressure or your operating distance from the wood.

DO NOT use "turbojets" on wood.

Rinse from the highest point and work down methodically using long even strokes in the direction of the grain.

Where pressure washing is not practical, rinse off with clean water from a bucket or a garden hose using a light scrubbing action with a stiff brush.

Clean-up: Equipment may be cleaned with water. Ensure wash water is disposed in accordance with local regulations

IMPORTANT INFORMATION

CUTEK® Quickclean is a powerful general-purpose outdoor cleaner. It easily removes dirt, grease and grime and is the perfect way to clean your wood in preparation for a maintenance coat of CUTEK® Extreme.

It is important for the user to determine the suitability of CUTEK® Quickclean for its intended application.

CUTEK® Quickclean should be used diluted. The dilution will vary depending on the type of surface being cleaned and the buildup of dirt/grease on the substrate.

ALWAYS test product on a small test area, referring to the dilution guidelines, before making a full mixture and applying to any large sections. As the substrates and conditions can vary significantly, testing will enable you to accurately estimate the dilution ratio, working time, and amount of CUTEK® Quickclean required to complete your project. It will also enable you to perfect the cleaning technique that works best for your situation.



STORAGE & SAFETY

SAFETY	Read the Safety Data Sheet and any precautions on container labels.
STORAGE	This product is NOT classified as dangerous goods for transport or storage in Canada. Store in well ventilated bunded area under cover and away from sources of heat. Keep containers closed at all times.
HANDLING	As with any chemical, ingestion, inhalation or contact with eyes and skin should be avoided by good occupational work practice. Eye protection approved to CAN/CSA Z94.3-15 and impervious rubber gloves should be worn where there is a risk of splashes entering the eyes or contacting the skin. Always wash hands before smoking, eating, drinking or using the toilet.
USING	Use with good ventilation and avoid inhalation of spray mists and fumes. If risk of inhalation of spray mists exists, wear combined organic vapour/particulate respirator.
FLAMMABILITY	This product is not flammable. On burning may emit toxic fumes.

CANADIAN LICENSE HOLDER

Deck Source Inc.
22 Winstar Rd, Unit 1
Oro-Medonte, ON, L0L 2L0

Contact:
1-844-442-8835

The data presented in this medium and any advice, recommendation, information, assistance or service provided by CUTEK[®] in relation to goods manufactured by it or their use and application is given in good faith and is believed by CUTEK[®] to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by CUTEK[®] does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from determining suitability of the product for their own purpose. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.