

CUTEK[®] WOOD STRIPPER

PROFESSIONAL WOOD AND SURFACE COATING STRIPPER



BENEFITS

- **Powerful wood stripper** – removes old surface coatings from wood, metal, brick and masonry surfaces
- **Smart alternative** – does not use dangerous chemicals like Methylene Chloride and NMP
- **Safe and user-friendly** – safe to use on your DIY project; no professional experience necessary

USES

CUTEK[®] Wood Stripper (formerly CUTEK[®] CD33 Naked) is a powerful and user-friendly paint and surface coating stripper. CUTEK[®] Wood Stripper is DIY-friendly; no professional experience is necessary.

CUTEK[®] Wood Stripper is suitable for removing multiple layers of the most commonly used wood coatings such as latex paints, stains, varnishes, linseed oils, acrylics and other film forming coatings. It is also effective at removing coatings from metal, brick and masonry surfaces.

Powerful yet safe, CUTEK[®] Wood Stripper is the smart alternative to conventional strippers that use dangerous chemicals (such as methylene chloride, NMP, etc.).

SPECIFICATIONS

TYPICAL PROPERTIES AND APPLICATION DATA

CLASSIFICATION	Paint stripper
COMPONENTS	One
FLASH POINT	> 100°C (212°F)
pH	8 as supplied
THINNER	Do not thin
PACK SIZES	1 US Gallon (3.78L)

SPREADING RATE

Spreading rate is approximately 1 gallon of CUTEK[®] Wood Stripper per 120ft² (1L/3m²) of surface area to be stripped.

NOTE: Practical spreading rates will vary depending on such factors as application method, ambient conditions and surface porosity and roughness.

CUTEK® WOOD STRIPPER



PREPARATION AND PROTECTION GUIDELINE

This is a guide only and not to be used as a specification. Contact CUTEK® to discuss your specific project requirements.

WOOD CONDITION/ DESIRED EFFECT	SITUATION	PREPARATION	PROTECTION	ADD CUTEK® COLORTONE? (Y/N)
OLD WOOD - Previously Coated in CUTEK® Extreme Stabilize & allow to naturally lighten/silver	Exterior	Remove previous coating with CUTEK® Wood Stripper then clean with CUTEK® Wood Reviver	Apply 2 coats of CUTEK® Extreme	N
OLD WOOD - Previously coated with film forming coating Retain freshly oiled look or alter the wood color	Exterior	Remove previous coating with CUTEK® Wood Stripper then clean with CUTEK® Wood Reviver	Apply 2 coats of CUTEK® Extreme	Y
OLD WOOD - Previously coated with film forming coating Stabilize & allow to naturally lighten/silver	Exterior	Remove previous coating with CUTEK® Wood Stripper then clean with CUTEK® Wood Reviver	Apply 2 coats of CUTEK® Extreme	N

CUTEK® WOOD STRIPPER



DIRECTIONS FOR USE

APPLICATION

APPLICATION PRECAUTIONS

Before you get started: Note the hazards and precautions on the CUTEK® website and the container labelling, and ensure that you use the correct safety equipment as detailed in the Safety Data Sheet.

It is also important to be aware of the potential for wind drift into areas with cars or pedestrian traffic when rinsing. Water flush all equipment, vegetation, paths, concrete, asphalt and other adjacent surfaces before and after contact.

A full list of application precautions is available on our website at www.cutekstain.com or by checking with customer services on 1-833-692-8835.

DO NOT SWALLOW.

CUTEK® Wood Stripper will make surfaces slippery, DO NOT walk on the surface until CUTEK® Wood Stripper has been removed.

Leave job site free of any trace amounts of CUTEK® Wood Stripper. Never leave behind any containers or equipment and appropriately label any containers of residual for disposal.

STEP BY STEP APPLICATION PROCESS:

Apply CUTEK® Wood Stripper evenly with a brush, roller or paint pad to dry wood, rubbing into the grain. Reaction time is approx. 30-60 minutes. Keep area wet and activated by applying more CUTEK® Wood Stripper or by agitating the application area with a brush, roller or paint pad.

Test periodically with a paint scraper to determine when the old coating is stripping cleanly off the lumber. When this happens, the stripped surface is ready for rinsing. We suggest that you try to strip only 10ft² first to perfect your technique.

Once CUTEK® Wood Stripper has loosened the coating, it must be power rinsed off thoroughly. For best results use a pressure washer set to approximately 50 bar (750 p.s.i.) with a fan jet pattern. Keep an operating distance of at least 4" from the wood.

REMOVAL WITH A GARDEN HOSE IS NOT SUFFICIENT.

CAUTION must be used to avoid damage to the wood fiber and 'furring up'. Adjust your cleaning process by reducing the pressure or your operating distance from the wood. DO NOT use "turbojets" on wood.

Clean from the lowest point and work upwards methodically using long even strokes in the direction of the grain. If cleaned from the highest point first, the product below can become sticky and difficult to remove.

After stripping the wood, clean your wood with CUTEK® Wood Reviver to remove residual CUTEK® Wood Stripper and rejuvenate the substrate.

Clean-up: Equipment may be cleaned with CUTEK® Quickclean or soap/detergent and water. All wash water, containers/contents should be disposed in accordance with local regulations.

IMPORTANT INFORMATION

CUTEK® Wood Stripper is a powerful and user-friendly paint/surface coating stripper. It is suitable for removing multiple layers of the most commonly used wood coatings such as latex paints, stains, varnishes, linseed oils, acrylics and other film forming coatings. It is also effective at removing coatings from metal, brick and masonry surfaces. Powerful yet safe, CUTEK® Wood Stripper is considered the smart alternative to conventional strippers that use dangerous chemicals (such as methylene chloride, NMP, etc.)

It is important for the user to determine the suitability of CUTEK® Wood Stripper for your intended application. ALWAYS test product on a small test area. The coatings to be stripped can vary significantly, testing will enable you to accurately estimate the working time, and amount of CUTEK® Wood Stripper required to complete your project. It will also enable you to perfect the technique that works best for your situation.

Note: CUTEK® Wood Stripper may need to be applied more than once to thick paint or film form coatings with many layers.