

**1. Identification**

<b>Product identifier</b>	<b>CUTEK® Extreme</b>	
<b>Other means of identification</b>	Not available.	
<b>Recommended use</b>	Decorative Wood Coating for Exterior Use	
<b>Recommended restrictions</b>	None known.	
<b>Manufacturer/Importer/Supplier/Distributor information</b>		
<b>Distributor</b>		
<b>Company name</b>	CUTEK America LLC	Deck Source Inc.
<b>Address</b>	6810 Tordera St Coral Gables, FL 33146 USA	22 Winstar Rd, Unit 1 Oro-Mednote, ON L0L 2E0 Canada
<b>Telephone</b>	1-833-MY-CUTEK (1-833-692-8835)	
<b>E-mail</b>	Not available.	
<b>Emergency phone number</b>	<b>EMERGENCY CONTACT:</b> 1-855-237-5573 <b>POISON CONTROL HOTLINE:</b> 1-800-222-1222	

**2. Hazard identification**

<b>Physical hazards</b>	Flammable liquids	Category 4
<b>Health hazards</b>	Sensitization, skin	Category 1
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Not classified.	
<b>WHMIS 2015 defined hazards</b>	Not classified	
<b>Label elements</b>		



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Combustible liquid. May cause an allergic skin reaction. May be fatal if swallowed and enters airways.
<b>Precautionary statement</b>	
<b>Prevention</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Contaminated work clothing should not be allowed out of the workplace. Avoid breathing vapors. Wear protective gloves, protective clothing, eye protection and face protection.
<b>Response</b>	In case of fire: Use dry sand, dry chemical, or alcohol resistant foam to extinguish. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on this label). IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
<b>Storage</b>	Store in a well-ventilated place. Store locked up.
<b>Disposal</b>	Dispose of container in accordance with local, regional, national and international regulations.
<b>WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)</b>	None known
<b>WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)</b>	None known
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	None.

### 3. Composition/Information on ingredients

#### Mixture

Chemical name	Common name and synonyms	CAS number	%
Octylisothiazolone		26530-20-1	0.09
Ethylbenzene		100-41-4	< 0.1
Alkyl (C12-14) glycidyl ether		68609-97-2	1 - 5 *
Butylcarbamic acid, 3-iodo-2-propynyl ester		55406-53-6	0.1 - 1 *
Distillates (petroleum), hydrotreated light paraffinic		64742-55-8	45 - 70 *
Naphtha (petroleum), hydrotreated heavy		64742-48-9	10 - 30 *

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

\*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
<b>Skin contact</b>	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.
<b>Eye contact</b>	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
<b>Ingestion</b>	IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation. May cause an allergic skin reaction. Dermatitis. Rash.
<b>Indication of immediate medical attention and special treatment needed</b>	Treat patient symptomatically.
<b>General information</b>	If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. Avoid contact with eyes and skin. Keep out of reach of children.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Dry chemical powder. Carbon dioxide. Foam.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire-fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Combustible liquid.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon.

### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Avoid breathing mist/vapor. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

**Methods and materials for containment and cleaning up**

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

---

## 7. Handling and storage

---

**Precautions for safe handling**

Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Provide adequate ventilation. Observe good industrial hygiene practices. Wash thoroughly after handling. When handling, do not eat, drink or smoke.

**Conditions for safe storage, including any incompatibilities**

Store in a cool, dry place out of direct sunlight. Keep away from heat, sparks and open flame. Store in tightly closed container. Store in a well-ventilated place. Store locked up. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

---

## 8. Exposure controls/Personal protection

---

**Occupational exposure limits****Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Ethylbenzene (CAS 100-41-4)	STEL	543 mg/m3	
	TWA	125 ppm 434 mg/m3 100 ppm	

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	525 mg/m3	

**Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

**Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)**

Components	Type	Value
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	15 minute	10 mg/m3
	8 hour	5 mg/m3
Ethylbenzene (CAS 100-41-4)	15 minute	125 ppm
	8 hour	100 ppm

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	PEL	5 mg/m3	Mist.
	PEL	435 mg/m3	
Ethylbenzene (CAS 100-41-4)		100 ppm	

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
	TWA	20 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	
	TWA	435 mg/m3 100 ppm	

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Safety glasses recommended but not required. Take prudent precautions to avoid contact with eyes.

**Skin protection**

**Hand protection**

Impervious gloves. Confirm with reputable supplier first.

**Other**

As required by employer code.

**Respiratory protection**

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

**Thermal hazards**

Not applicable.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke.

---

**9. Physical and chemical properties**

---

<b>Appearance</b>	Liquid
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Amber / Green
<b>Odor</b>	Not available.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not available.
<b>Pour point</b>	Not available.
<b>Specific gravity</b>	0.86 @ 21°C
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Flash point</b>	179.6 °F (82.0 °C) ASTM D93
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	18 cSt @ 40°C
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.
<b>VOC</b>	215 g/l ASTM D2369

---

**10. Stability and reactivity**

---

<b>Reactivity</b>	This product may react with strong oxidizing agents.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Do not mix with other chemicals.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	May include and are not limited to: Oxides of carbon.

---

**11. Toxicological information**

---

<b>Routes of exposure</b>	Eye, Skin contact, Inhalation, Ingestion.
<b>Information on likely routes of exposure</b>	
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May cause stomach distress, nausea or vomiting.
<b>Inhalation</b>	Prolonged inhalation may be harmful.

**Skin contact** May cause an allergic skin reaction.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Symptoms related to the physical, chemical and toxicological characteristics** Aspiration may cause pulmonary edema and pneumonitis. May cause an allergic skin reaction. Dermatitis. Rash.

**Information on toxicological effects**

**Acute toxicity** May be fatal if swallowed and enters airways.

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
Alkyl (C12-14) glycidyl ether (CAS 68609-97-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rat	4000 mg/kg, ECHA
<i>Inhalation</i>		
LC50	Rat	0.2 mg/L, 7 h, ECHA
<i>Oral</i>		
LD50	Rat	> 2000 mg/kg, ECHA 30.1 ml/kg, ECHA
Butylcarbamic acid, 3-iodo-2-propynyl ester (CAS 55406-53-6)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, HSDB
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Rat	1500 mg/kg, HSDB 1100 mg/kg, HSDB
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.5 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Ethylbenzene (CAS 100-41-4)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	17.8 ml/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	17629 mg/m <sup>3</sup> , 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	3500 mg/kg, ECHA
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 1900 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Octylisothiazolone (CAS 26530-20-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	690 mg/kg

Components	Species	Test Results
<i>Inhalation</i>		
LC50	Rat	
<i>Oral</i>		
LD50	Rat	550 mg/kg
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	
<b>Oedema value</b>	Not available.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Corneal opacity value</b>	Not available.	
<b>Iris lesion value</b>	Not available.	
<b>Conjunctival reddening value</b>	Not available.	
<b>Conjunctival oedema value</b>	Not available.	
<b>Recover days</b>	Not available.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	May cause an allergic skin reaction.	
<b>Mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	Contains < 3% (w/w) DMSO-extract	
<b>ACGIH Carcinogens</b>		
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	A2	Suspected human carcinogen.
Ethylbenzene (CAS 100-41-4)	A3	Confirmed animal carcinogen with unknown relevance to humans.
<b>California Proposition 65 - CRT: Listed date/Carcinogenic substance</b>		
Ethylbenzene (CAS 100-41-4)		
<b>Canada - Manitoba OELs: carcinogenicity</b>		
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Suspected human carcinogen.	
Ethylbenzene (CAS 100-41-4)	Confirmed animal carcinogen with unknown relevance to humans.	
<b>Canada - Quebec OELs: Carcinogen category</b>		
Ethylbenzene (CAS 100-41-4)	Detected carcinogenic effect in animals.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Ethylbenzene (CAS 100-41-4)	Volume 77 - 2B Possibly carcinogenic to humans.	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	Volume 47 - 3 Not classifiable as to carcinogenicity to humans.	
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)</b>		
Not listed.		
<b>US NTP Report on Carcinogens: Known carcinogen</b>		
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Known To Be Human Carcinogen.	
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.	
<b>Teratogenicity</b>	Not available.	
<b>Specific target organ toxicity - single exposure</b>	Not classified.	
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Chronic effects</b>	Prolonged inhalation may be harmful.	

## 12. Ecological information

<b>Ecotoxicity</b>	See below
--------------------	-----------

**Ecotoxicological data**

<b>Components</b>		<b>Species</b>	<b>Test Results</b>
Butylcarbamic acid, 3-iodo-2-propynyl ester (CAS 55406-53-6)			
<b>Aquatic</b>			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.05 - 0.089 mg/L, 96 hours
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)			
Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours
Ethylbenzene (CAS 100-41-4)			
Algae	IC50	Algae	4.6 mg/L, 72 Hours
Crustacea	EC50	Daphnia	2.1 mg/L, 48 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/L, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/L, 96 hours
<b>Persistence and degradability</b>	No data is available on the degradability of any ingredients in the mixture.		
<b>Bioaccumulative potential</b>			
<b>Mobility in soil</b>	No data available.		
<b>Mobility in general</b>	Not available.		
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

---

**13. Disposal considerations**

---

<b>Disposal instructions</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

**14. Transport information**

---

**Transport of Dangerous Goods (TDG) Proof of Classification** Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

**U.S. Department of Transportation (DOT)**

Not regulated as dangerous goods.

**Transportation of Dangerous Goods (TDG - Canada)**

Not regulated as dangerous goods.

---

**15. Regulatory information**

---

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

**Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number**

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) 1 TONNES

**Export Control List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

Not listed.

**Precursor Control Regulations**

Not regulated.

**WHMIS 2015 Exemptions** Not applicable

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.



**CERCLA Hazardous Substance List (40 CFR 302.4)**

Ethylbenzene (CAS 100-41-4) Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)****SARA 302 Extremely hazardous substance** No**SARA 311/312 Hazardous chemical** Yes**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
Respiratory or skin sensitization  
Aspiration hazard**SARA 313 (TRI reporting)**

Not regulated.

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethylbenzene (CAS 100-41-4)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**US state regulations** See below**US - California Hazardous Substances (Director's): Listed substance**

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.

Ethylbenzene (CAS 100-41-4) Listed.

**US - Illinois Chemical Safety Act: Listed substance**

Ethylbenzene (CAS 100-41-4)

**US - Louisiana Spill Reporting: Listed substance**

Ethylbenzene (CAS 100-41-4) Listed.

**US - Minnesota Haz Subs: Listed substance**

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.

Ethylbenzene (CAS 100-41-4) Listed.

**US - Texas Effects Screening Levels: Listed substance**

Butylcarbamic acid, 3-iodo-2-propynyl ester (CAS 55406-53-6) Listed.

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.

Ethylbenzene (CAS 100-41-4) Listed.

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Listed.

Octylisothiazolone (CAS 26530-20-1) Listed.

**US - Washington Chemical of High Concern to Children: Listed substance**

Ethylbenzene (CAS 100-41-4)

**US. Massachusetts RTK - Substance List**

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

Ethylbenzene (CAS 100-41-4)

**US. New Jersey Worker and Community Right-to-Know Act**

Butylcarbamic acid, 3-iodo-2-propynyl ester (CAS 55406-53-6)

Ethylbenzene (CAS 100-41-4)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

Ethylbenzene (CAS 100-41-4)

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

**US. Rhode Island RTK**

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

Ethylbenzene (CAS 100-41-4)

**US. California Proposition 65****WARNING:** This product can expose you to chemicals including ethylbenzene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Ethylbenzene (CAS 100-41-4)

Listed: June 11, 2004

**Inventory status**


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**16. Other information**

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

<b>HEALTH</b>	* 1
<b>FLAMMABILITY</b>	2
<b>PHYSICAL HAZARD</b>	0
<b>PERSONAL PROTECTION</b>	X



**Disclaimer**

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

**Issue date**

03-December-2021

**Version #**

01

**Effective date**

03-December-2021

**Prepared by**

Dell Tech Laboratories, Ltd. Phone: (519) 858-5021

**Further information**

Not available.

**Other information**

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.