

CUTEK® WOOD STRIPPER

PROFESSIONAL SURFACE COATING STRIPPER



CUTEK® Wood Stripper (formerly CUTEK® CD33 Naked) is a powerful and user-friendly paint and surface coating stripper. CUTEK® Wood Stripper is DIY-friendly; no professional experience is necessary.

CUTEK® Wood Stripper is suitable for removing multiple layers of the most commonly used wood coatings such as latex paints, stains, varnishes, linseed oils, acrylics and other film-forming coatings. It is also effective at removing coatings from metal, brick and masonry surfaces.

Powerful yet safe, CUTEK® Wood Stripper is the smart alternative to conventional strippers that use dangerous chemicals (such as methylene chloride, NMP, etc.).

WHY CUTEK® WOOD STRIPPER?

- **Powerful wood stripper** – removes old surface coatings from timber, metal, brick and masonry surfaces
- **Smart alternative** – does not use dangerous chemicals like Methylene Chloride and NMP
- **Safe and user-friendly** – safe to use on your DIY project; no professional experience necessary.

CUTEK® WOOD STRIPPER

DIRECTIONS FOR USE

WHAT YOU WILL NEED



Paint tray/pot



Brush, roller
or lambswool
applicator



Paint Scraper



CUTEK® Restore



Soap/Detergent



Pressure
Washer

COVERAGE

Spreading rate is approximately 1 litre of CUTEK® Wood Stripper per 3m² of surface area to be stripped.

Note: this can vary significantly depending on the type and thickness of the paint or wood coating being removed.

IMPORTANT INFORMATION

CUTEK® Wood Stripper is a powerful and user-friendly paint/surface coating stripper. It is suitable for removing multiple layers of the most commonly used wood coatings such as latex paints, stains, varnishes, linseed oils, acrylics and other film forming coatings. It is also effective at removing coatings from metal, brick and masonry surfaces. Powerful yet safe, CUTEK® Wood Stripper is considered the smart alternative to conventional strippers that use dangerous chemicals (such as methylene chloride, NMP, etc.)

Because of the variations in coatings to be stripped, it is vital to test CUTEK® Wood Stripper BEFORE starting your project. This will help you determine how much time you will need to leave CUTEK® Wood Stripper on the timber and how much product you will need for the job.

Note: CUTEK® Wood Stripper may need to be applied more than once to thick paint or film-forming coatings with many layers.

CUTEK® WOOD STRIPPER

PRECAUTIONS

Before you begin to Prepare and Protect your timber, note the hazards and precautions and ensure that you have obtained and know how to use the correct safety equipment. CUTEK® Wood Stripper is a hazardous chemical. It is important to refer to the health and safety considerations listed in the Safety Data Sheet (SDS) prior to commencement of your project. When using CUTEK® Wood Stripper all adjacent surfaces and vegetation must be adequately protected.

It is also important to be aware of the potential for wind drift into areas with cars or pedestrian traffic when rinsing. Water flush all equipment, vegetation, paths, concrete, asphalt and other adjacent surfaces before and after contact. Leave job site free of any trace amounts of CUTEK® Wood Stripper. Never leave behind any containers or equipment and appropriately label any containers of residual for disposal.

DO NOT SWALLOW.

For best results use CUTEK® Wood Stripper as supplied and stir/shake well before use.

A full list of precautions and the SDS is available at www.cutekwoodsolutions.com

STEP 1 ▶ PREPARE

APPLICATION: Apply CUTEK® Wood Stripper evenly with a brush, roller or lambswool applicator to dry wood, rubbing into the grain. Reaction time is approx. 30–60 minutes. Keep area wet and activated by applying more CUTEK® Wood Stripper or by agitating the application area with a brush, roller or lambswool applicator. CUTEK® Wood Stripper makes surfaces slippery so DO NOT walk on the application area until CUTEK® Wood Stripper has been removed.

Test periodically with a paint scraper to determine when the old coat is stripping cleanly off the timber. When this happens, the stripped surface is ready for rinsing. We suggest that you try to strip only 1 square metre first to perfect your technique.

REMOVAL: Once CUTEK® Wood Stripper has loosened the coating, it must be power rinsed off thoroughly. For best results, power rinse with a high-pressure washer set to approximately 50 bar (750 p.s.i.) with a fan jet pattern.

REMOVAL WITH A GARDEN HOSE IS NOT SUFFICIENT.

CAUTION must be used when cleaning soft timber. Reduce the pressure or adjust distance from the substrate to avoid damaging the sapwood. It is important to adjust your cleaning process as to avoid damage to the wood fibre. Clean from the lowest point and work upwards methodically using long even strokes in the direction of the grain. DO NOT use “turbojets” on timber. Certain types of wood surfaces may leave a raised grain effect after stripping is completed. Sanding or poly pad scrubbing may be required to smooth out this condition.

After stripping the timber, clean your wood with CUTEK® Restore to remove residual CUTEK® Wood Stripper and rejuvenate the substrate and enhance the grain. See CUTEK® Restore for instructions.

CLEAN UP & DISPOSAL: Equipment may be cleaned with CUTEK® Quickclean or soap/detergent and water. All wash water, containers/contents should be disposed in accordance with local regulations.

CUTEK® WOOD STRIPPER

STEP 2 ▶ PROTECT

Following the removal of paint or wood coating, rejuvenate your timber with CUTEK® Restore and complete the restoration process by protecting your timber with a CUTEK® wood oil after ensuring the rejuvenated wood is completely dry with a moisture content less than 17% (this typically takes 2-3 days, however, this time can vary depending on ventilation and weather exposure).

Designed for and proven to work in the harshest of Australian environments, CUTEK® wood oils penetrate and diffuse deeply into the wood core to protect against liquid and gas phase moisture and extend service life:



CUTEK® EXTREME

Suitable for interior walls and ceilings, and external timber. High performance penetrating oil stabiliser that works from the inside out to control moisture and minimise warping, cupping and splitting.



CUTEK® CD50

Suitable for external use only. High performance penetrating oil stabiliser that works from the inside out to control moisture and minimise warping, cupping and splitting.



CUTEK® Wood Preservative

Oil-based wood stabiliser used for the pre-treatment and remedial treatment of exterior wood in industrial and domestic situations. CUTEK® Wood Preservative coated wood resists damage caused by fungal decay, mould, termites and controls moisture to improve dimensional stability and minimise cupping, warping and splitting.

Maintenance with CUTEK® wood oil is simple, easy and cost effective. Simply clean and recoat – no need to sand or strip.

Not protecting your timber with a CUTEK® wood oil after cleaning will result in water damage and a faster weathering/greying process when exposed to the weather.

For other hints, tricks and videos on how to use CUTEK® Prepare and Protect products, visit the CUTEK® website: cutekwoodsolutions.com