CUTEK Quickclean

Safety Data Sheet

According to SOR/2015-17, Hazardous Products Regulations (HPR) (amended 2022) & According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) (amended 2024)
Issue date: 02/27/2026 Version: 1.0

SECTION 1 Identification

1.1. GHS Product identifier

Product form : Mixture
Product name : CUTEK Quickclean

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Multi-Purpose Cleaner

1.4. Supplier's details

Manufacturer
CUTEK Canada
22 Winstar Rd, Unit 1
Medonte, ON, L0L 2E0
Canada
T 1-844-44-CUTEK (1-844-442-8835)
inquiries@cutekws.com

1.5. Emergency phone number

Emergency number : 1-867-670-2867

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA/US)

Skin corrosion/irritation, Category 2	Causes skin irritation.
Serious eye damage/eye irritation, Category 2A	Causes serious eye irritation.

2.2. GHS label elements, including precautionary statements

GHS CA/US labeling

Hazard pictograms (GHS CA/US) :

Signal word (GHS CA/US) : Warning

Hazard statements (GHS CA/US) : Causes skin irritation
Causes serious eye irritation

Precautionary statements (GHS CA/US) : Wash hands, forearms and face thoroughly after handling.
Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
IF ON SKIN: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice or attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice or attention.
Specific treatment (see supplemental first aid instruction on this label).

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
2-Butoxyethanol	2-butoxyethanol; ethylene glycol monobutyl ether 2-Butoxy-1-ethanol / Butoxyethanol / Ethanol, 2-butoxy- / Ethylene glycol monobutyl ether / Ethylene glycol n-butyl ether / Hydroxyethyl butyl ether / Ethylene glycol butyl ether / 2-Butoxyethan-1-ol / Ethylene glycol mono-n-butyl ether / 2-n-Butoxyethanol / Butyl glycol / BUTOXYETHANOL / EGBE / EGMBE / Butoxyethanol, 2- / Butyl Cellosolve / Monobutyl ether of ethyleneglycol	CAS-No.: 111-76-2	7 - 13
Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C12-14-alkyl ethers, sodium salts	Alcohols, C12-14, ethoxylated, sulfates, sodium salts / Polyethylene glycol mono-C12-14-alkyl ether sulfate sodium salt / Poly(oxyethylene), .alpha.-sulfo-.omega.-hydroxy-, C12-14-alkyl ethers, sodium salts / Sodium C12-14 pareth-3 sulfate / SODIUM C12-14 ALKETH-3 SULFATE	CAS-No.: 68891-38-3	5 - 10

Comments : CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with the amended HPR as of December 2022.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice or attention.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

First-aid measures after ingestion : Do not induce vomiting. If vomiting occurs have person lean forward. Never give anything by mouth to an unconscious person. Call a poison center or a doctor if you feel unwell.

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible). Medical personnel should be made aware of substance(s) involved and take measures for self protection. Show this safety data sheet to the doctor in attendance. Avoid contact with skin and eyes. Keep out of the reach of children.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : Prolonged inhalation may be harmful.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Symptoms/effects after ingestion : May cause stomach distress, nausea or vomiting.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Symptoms may be delayed. Treat symptomatically.

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Treat for surrounding material.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Specific hazards arising from the chemical

Fire hazard : During fire, gases hazardous to health may be formed. In case of fire or explosion do not breathe fumes.

Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : May include and are not limited to: oxides of carbon.

5.3. Special protective actions for fire-fighters

Firefighting instructions : In case of fire: Stop leak if safe to do so. Do not enter fire area without proper protective equipment, including respiratory protection. Move containers from fire area if it can be done without personal risk.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : In the event of a significant spillage : Notify authorities if product enters sewers or public waters. Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leaks if it can be done without personal risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Clean contaminated surfaces with an excess of water.

Other information : This material and its container must be disposed of in a safe way, and as per local legislation.

For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing vapors. Do not taste or swallow. Ensure good ventilation of the work station. Wear personal protective equipment. Handle and open container with care.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of reach of children. Store tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

2-Butoxyethanol (111-76-2)	
Canada (Alberta) - Occupational Exposure Limits	
OEL TWA	97 mg/m³
	20 ppm
Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
VEMP (OEL TWAEV)	20 ppm
Notations and remarks	C3
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
OEL TWA	20 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
OEL TWA	97 mg/m³
	20 ppm
Notations and remarks	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2025
Canada (New Brunswick) - Occupational Exposure Limits	
OEL TWA	20 ppm

2-Butoxyethanol (111-76-2)	
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
OEL TWA	97 mg/m³
	20 ppm
Notations and remarks	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
OEL TWA	97 mg/m³
	20 ppm
Notations and remarks	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
OEL TWA	20 ppm
OEL STEL	30 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
OEL TWA	20 ppm
OEL STEL	30 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
OEL TWAEV	20 ppm
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
OEL TWA	97 mg/m³
	20 ppm
Notations and remarks	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
OEL TWA	20 ppm
OEL STEL	30 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Canada (Yukon) - Occupational Exposure Limits	
OEL TWA	240 mg/m³
	50 ppm
OEL STEL	720 mg/m³

2-Butoxyethanol (111-76-2)	
	150 ppm
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	97 mg/m³
	20 ppm
Remark (ACGIH®)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH® chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2025
USA - ACGIH® - Biological Exposure Indices	
Local name	2-Butoxyethanol (EGBE)
BEI	200 mg/g Kreatinin Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	240 mg/m³
	50 ppm
Limit value category (OSHA)	prevent or reduce skin absorption
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection:
Wear suitable gloves resistant to chemical penetration

Eye protection:
Wear safety glasses with side shields (or goggles).

Skin and body protection:
Wear suitable protective clothing. As required by employer code.

Respiratory protection:
Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	:	Liquid
Appearance	:	No data available
Color	:	No data available
Odor	:	No data available
Odor threshold	:	No data available
pH	:	12.25 (0.118 g NaOH/100mL)
Relative evaporation rate (butyl acetate=1)	:	No data available
Relative evaporation rate (ether=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	No data available
Vapor pressure	:	No data available
Relative vapor density at 20°C	:	No data available
Relative density	:	1.01
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Viscosity, kinematic	:	7.5 mm²/s
Explosive properties	:	Not explosive.
Oxidizing properties	:	Not oxidising.
Explosion limits	:	No data available
Particle characteristics	:	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

Reactivity	:	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No dangerous reactions known under normal conditions of use.
Conditions to avoid	:	Keep away from heat and direct sunlight. Do not mix with other chemicals.
Incompatible materials	:	Strong oxidizing agents.
Hazardous decomposition products	:	May include and are not limited to: oxides of carbon.

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

2-Butoxyethanol (111-76-2)	
LD50 oral rat	470 mg/kg (Source: NLM_CIP)
LD50 oral	1414 mg/kg body weight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rabbit	435 mg/kg (Source: OECD_SIDS)

2-Butoxyethanol (111-76-2)	
LC50 Inhalation - Rat [ppm]	486 ppm/4h
ATE CA (oral)	470 mg/kg body weight
ATE CA (Dermal)	435 mg/kg body weight
ATE CA (Gases)	486 ppmV/4h
ATE CA (vapors)	3 mg/l/4h

Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C12-14-alkyl ethers, sodium salts (68891-38-3)	
LD50 oral rat	4100 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
ATE CA (oral)	4100 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.
pH: 12.25 (0.118 g NaOH/100mL)

Serious eye damage/irritation : Causes serious eye irritation.
pH: 12.25 (0.118 g NaOH/100mL)

Respiratory or skin sensitization : Skin sensitization: Not classified.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

2-Butoxyethanol (111-76-2)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

2-Butoxyethanol (111-76-2)	
NOAEL (dermal,rat/rabbit,90 days)	> 150 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C12-14-alkyl ethers, sodium salts (68891-38-3)	
LOAEL (oral,rat,90 days)	25 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral,rat,90 days)	> 225 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard : Not classified

Likely routes of exposure : Skin and eye contact. Ingestion. Inhalation.

Symptoms/effects after inhalation : Prolonged inhalation may be harmful.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Symptoms/effects after ingestion : May cause stomach distress, nausea or vomiting.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general : See below for route-specific details.

Hazardous to the aquatic environment, short–term (acute) : Not classified.

Hazardous to the aquatic environment, long–term (chronic) : Not classified.

2-Butoxyethanol (111-76-2)	
LC50 - Fish [1]	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
LC50 - Fish [2]	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus Source: IUCLID)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C12-14-alkyl ethers, sodium salts (68891-38-3)	
LC50 - Fish [1]	7.1 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Flow-through system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	7.4 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	28 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
EC50 72h - Algae [1]	27.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC chronic fish	0.14 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '28 d'
NOEC (chronic)	0.27 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

CUTEK Quickclean	
Persistence and degradability	Not rapidly degradable

2-Butoxyethanol (111-76-2)	
Persistence and degradability	Rapidly degradable

Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C12-14-alkyl ethers, sodium salts (68891-38-3)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

2-Butoxyethanol (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (at 25 °C (at pH 7)

Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C12-14-alkyl ethers, sodium salts (68891-38-3)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	0.3 (at 23 °C (at pH 6.1)

12.4. Mobility in soil

Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C12-14-alkyl ethers, sodium salts (68891-38-3)	
Surface tension	33 mN/m (25 °C, 0.07 %, BS EN 14370:2004: Surface tension)

Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C12-14-alkyl ethers, sodium salts (68891-38-3)	
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.34 (log Koc, QSAR)

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Waste treatment methods : Dispose of the material collected according to regulations.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal recommendations : Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling, disposal or collection.

SECTION 14 Transport information

In accordance with TDG / DOT

General information: For additional information or clarification regarding the transport classification of this product, please contact the manufacturer.

TDG	DOT
14.1. UN Number	
Not regulated	Not regulated
14.2. UN Proper Shipping Name	
Not regulated	Not regulated
14.3. Transport hazard class(es)	
Not regulated	Not regulated
14.4. Packing group, if applicable	
Not regulated	Not regulated
14.5. Environmental hazards	
Not regulated	Not regulated
No supplementary information available	

14.6. Special precautions for user

TDG

Not regulated

DOT

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/789(^9) and the IBC Code(^10)

Not applicable

SECTION 15 Regulatory information

All components of this product are present on DSL, except for:

Amides, vegetable-oil, N,N-bis(hydroxyethyl) (68155-26-0)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Benzenesulfonic acid, 3,3'-[(9,10-dihydro-9,10-dioxo-1,4-anthracenediyl)diimino]bis[2,4,6-trimethyl-, disodium salt (Trade secret)

Not listed on the Canadian DSL (Domestic Substances List)
Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

2-Butoxyethanol (111-76-2)	
Toxic Substance (CEPA – Schedule I)	Yes

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Diethanolamine (111-42-2)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	100 lb

WARNING: This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	**State or local regulations**
2-Butoxyethanol(111-76-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Diethanolamine(111-42-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Sodium nitrate(7631-99-4)	U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List

SECTION 16 Other Information

Issue date	:	02/27/2026
Other information	:	For an updated SDS, please contact the supplier or manufacturer listed on the first page of the document.

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.