

# CUTEK® COLOURTONE



Note: These colours are an indication only. Colour may vary depending on multiple factors, including application and the condition and species of timber.

Enhance and maintain the natural colour of timber, or alter the colour entirely to meet design requirements with CUTEK® Colourtones.



Our transparent CUTEK® Colourtones **highlight rather than obscure** the natural grain and beauty of wood



Choose from our extensive range of **Colourtones**



Adding a Colourtone to clear CUTEK® wood oils provides **additional UV protection**

CUTEK® Colourtones are designed to work with CUTEK® wood oils to enhance the natural colour of timber and provide additional UV protection to timber, or alter the colour entirely to match your project.

Choose one of our CUTEK® Colourtones which have

been specifically developed to closely match many popular wood species. For best results, select a CUTEK® Colourtone that stays close to the natural shade of the coated timber. View the extensive colour chart on real timbers at our website [www.cutekwoodsolutions.com](http://www.cutekwoodsolutions.com) to see which CUTEK® Colourtone is right for your timber project.

CUTEK® Colourtones are only to be used with CUTEK® wood oils and are not compatible with and must not be mixed into CUTEK® Interior or any third-party product.

All CUTEK® wood oils are sold as clear, and if applied without an added Colourtone they will cause the timber to quickly lighten into a beautiful silver patina on exposure to sunlight and UV.

# CUTEK® COLOURTONE

## CHOOSING THE RIGHT CUTEK® COLOURTONE

To maintain the timber's natural colour for longer, choose a CUTEK® Colourtone similar to the natural colour of the timber. Suggested CUTEK® Colourtones that match the natural hue of your timber can be found in our tables below. Colourtones can also help alter your timber colour if required (e.g. make your timber look lighter or darker than its natural state). Always obtain a free CUTEK® Sample to check your colour choice before proceeding with your project.



AUTUMNTONE



BLACK ASH



BURNT RED



DUSKY BROWN



GOLDTONE



GREY MIST



HONEYCOMB



NEW BRONZETONE



RUSTIC GOLD



SELA BROWN



WHITE WASH



WALNUT

Note: These colours are an indication only. Colour may vary depending on many factors including application and the condition and species of timber. **We recommend you always try a free sample.**

Other CUTEK® Colourtones are available by special order.

## APPLICATION

Stir the contents of the CUTEK® Colourtone thoroughly and add to clear CUTEK® oil as follows:

1L CUTEK® oil	<b>Single mixture:</b> add 36mL Colourtone	<b>Double mixture:</b> add 36mL Colourtone
5L CUTEK® oil	<b>Single mixture:</b> add 1 Colourtone tube	<b>Double mixture:</b> add 2 Colourtone tubes
10L CUTEK® oil	<b>Single mixture:</b> add 2 Colourtone tube	<b>Double mixture:</b> add 4 Colourtone tubes
20L CUTEK® oil	<b>Single mixture:</b> add 4 Colourtone tube	<b>Double mixture:</b> add 8 Colourtone tubes

Thoroughly stir combined mixture from the bottom of the can BEFORE AND DURING use. Failure to do this may result in inconsistent colour.

For best results, one coat of clear CUTEK® timber oil should be applied to all faces of the wood prior to installing, with a second and third coat of Colourtoned CUTEK® timber oil applied to the top surface once the first coat is completely dry and non-greasy.

## MAINTENANCE

With CUTEK®, maintenance is simple, fast, and cost effective. CUTEK® timber oils will not crack, peel or split, and your wood can be easily rejuvenated or restored using our Prepare and Protect system - no need to sand or strip.

### Exterior timber

CUTEK® oils should be reapplied when the wood is no longer beading water, or as frequently as necessary to retain the beauty and colour of the wood. Typically, horizontal exterior wood surfaces exposed to full weather such as pool decks and handrails will require re-coating more frequently (initially after 6 months, then annually), while other surfaces such as vertical rough-sawn cladding will need recoating less often.

### Interior timber

CUTEK® oils used in interior settings (CUTEK® Extreme) should not require reapplication where there is no UV exposure. If you desire to refresh the colour of the wood, lightly clean the timber and apply one thin maintenance coat of clear or Colourtoned CUTEK® oil. If basic cleaning is required, use warm, mild soapy water and a soft dishcloth.

For other hints, tricks and videos on how to use CUTEK® Prepare and Protect products, visit the CUTEK® website: [cutekwoodsolutions.com](http://cutekwoodsolutions.com)