

CUTEK® WOOD STRIPPER



CUTEK® Wood Stripper (formerly CUTEK® CD33 Naked) is a powerful and user-friendly paint and surface coating stripper. CUTEK® Wood Stripper is DIY-friendly; no professional experience is necessary.



Powerful wood stripper – removes old surface coatings from timber, metal, brick and masonry surfaces



Smart alternative – does not use dangerous chemicals like Methylene Chloride and NMP



Safe and user-friendly – safe to use on your DIY project; no professional experience necessary.

CUTEK® Wood Stripper is suitable for removing multiple layers of the most commonly used wood coatings such as latex paints, stains, varnishes, linseed oils, acrylics and other film-forming coatings. It is also effective at removing coatings from metal, brick and masonry surfaces.

Powerful yet safe, CUTEK® Wood Stripper is the smart alternative to conventional strippers that use dangerous chemicals (such as methylene chloride, NMP, etc.).

CUTEK[®] WOOD STRIPPER

COVERAGE

Spreading rate is approximately 1 litre of CUTEK[®] Wood Stripper per 3m² of surface area to be stripped

Note: this can vary significantly depending on the type and thickness of the paint or wood coating being removed.

IMPORTANT INFORMATION

CUTEK[®] Wood Stripper is a powerful and user-friendly paint/surface coating stripper. It is suitable for removing multiple layers of the most commonly used wood coatings such as latex paints, stains, varnishes, linseed oils, acrylics and other film forming coatings. It is also effective at removing coatings from metal, brick and masonry surfaces. Powerful yet safe, CUTEK[®] Wood Stripper is considered the smart alternative to conventional strippers that use dangerous chemicals (such as methylene chloride, NMP, etc.)

Because of the variations in coatings to be stripped, it is vital to test CUTEK[®] Wood Stripper BEFORE starting your project. This will help you determine how much time you will need to leave CUTEK[®] Wood Stripper on the timber and how much product you will need for the job.

Note: CUTEK[®] Wood Stripper may need to be applied more than once to thick paint or film-forming coatings with many layers.

PRECAUTIONS

Before you begin to Prepare and Protect your timber, note the hazards and precautions and ensure that you have obtained and know how to use the correct safety equipment. CUTEK[®] Wood Stripper is a hazardous chemical. It is important to refer to the health and safety considerations listed in the Safety Data Sheet (SDS) prior to commencement of your project. When using CUTEK[®] Wood Stripper all adjacent surfaces and vegetation must be adequately protected.

It is also important to be aware of the potential for wind drift into areas with cars or pedestrian traffic when rinsing.

Water flush all equipment, vegetation, paths, concrete, asphalt and other adjacent surfaces before and after contact.

Leave job site free of any trace amounts of CUTEK[®] Wood Stripper. Never leave behind any containers or equipment and appropriately label any containers of residual for disposal.

DO NOT SWALLOW.

For best results use CUTEK[®] Wood Stripper as supplied and stir/shake well before use.

A full list of precautions and the SDS is available at www.cutekwoodsolutions.com