

# CUTEK® QUICKCLEAN

GENERAL PURPOSE OUTDOOR CLEANER CONCENTRATE  
D390



## BENEFITS

- **Powerful outdoor cleaner** – general-purpose cleaner that removes dirt, grease and grime from outdoor surfaces
- **Perfect for regular timber cleaning** – prepares timber for a maintenance coat of CUTEK® wood oils
- **Clean up CUTEK® spills with ease** – easily cleans accidental spills of CUTEK® wood oils
- **Cleans all hard surfaces** – including composite decking, plastic, PVC, tiles, pavers, concrete and glass.

## USES

CUTEK® Quickclean is a powerful general-purpose outdoor cleaner that removes dirt grease and grime from all your exterior hard surfaces.

It will easily remove dirt, grease, and grime as well as even out CUTEK® Colourtone that has started to wear or erode unevenly on your wood.

It is the perfect way to regularly keep all your wood clean, and it prepares wood to optimise the performance of maintenance coats of CUTEK® wood oils

CUTEK® Quickclean is a concentrate that should be diluted with water. The dilution will vary depending on the build-up of dirt/grease on the surface.

## SPECIFICATIONS

### TYPICAL PROPERTIES AND APPLICATION DATA

CLASSIFICATION	Industrial grade general purpose cleaner/degreaser
COMPONENTS	One
FLASH POINT	NA
pH	~13 as supplied
THINNER	May be thinned with water up to 1:100 V/V recommended start point is 1:8 V/V
PACK SIZES	2.5L, 5L, 10L, 200L, 1000L
PRODUCT CODE	D390



## SUBSTRATE GUIDE

This is a guide only and not to be used as a specification. Contact CUTEK® to discuss your specific project requirements.

SURFACE TYPE/ DESIRED EFFECT	SITUATION	PREPARATION	PROTECTION	ADD COLOURTONE? (Y/N)
Wood – new Retain freshly oiled look or alter the wood colour	Exterior	Clean with CUTEK® Restore if tannin/water/ iron stained	Apply 2 coats of CUTEK® wood oils.	Y
		Otherwise clean with CUTEK® Quickclean		Y
Wood – new Stabilise & allow to naturally lighten/silver	Exterior	Clean with CUTEK® Restore if tannin/water/ iron stained	Apply 2 coats of CUTEK® wood oils.	N
		Otherwise clean with CUTEK® Quickclean		N
Wood – old Previously coated with CUTEK® wood oils.	Exterior	Clean with CUTEK® Restore if tannin/water/iron stained	Apply 1 coat of CUTEK® wood oils.	Y
		Otherwise clean with CUTEK® Quickclean		

## SPREADING RATE

All surfaces: 4-7 sqm/L

NOTE: Practical spreading rates will vary depending on such factors as application method, ambient conditions and surface porosity and roughness.

## COVERAGE & DILUTION

PURPOSE	DILUTION (RECOMMENDED)	COVERAGE
Remove grease, oil, dirt and grime	1:8 1 part CUTEK® Quickclean to every 8 parts water	4-7 sqm/L (diluted)
Prepare timber pre-oiled with a different oil than CUTEK®	1:1 1 part CUTEK® Quickclean to 1 part Water (approx.)	5-10 sqm/L (diluted)

IMPORTANT: These figures represent typical averages for common decking and cladding species and are to be used as a guideline only.



## DIRECTIONS FOR USE

### APPLICATION

#### APPLICATION PRECAUTIONS

**Before you get started:** Before you begin, note the hazards and precautions on the CUTEK® website and the can labelling, and ensure that you use the correct safety equipment as detailed in the Safety Data Sheet.

When using CUTEK® Quickclean, all adjacent surfaces and vegetation must be adequately protected. It is also important to be aware of the potential for wind drift into areas with cars or pedestrian traffic when rinsing. Water flush all equipment, vegetation, paths, concrete, asphalt and other adjacent surfaces before and after contact.

Full list of application precautions is available on website at [www.cutekwoodsolutions.com](http://www.cutekwoodsolutions.com), or by checking with customer services on 1300 128835.

DO NOT SWALLOW.

#### STEP BY STEP APPLICATION PROCESS:

Dilute the CUTEK® Quickclean concentrate with water as required and complete a test patch to ensure that the dilution being used is effective in cleaning. Wet your substrate with water prior to applying CUTEK® Quickclean. Apply diluted CUTEK® Quickclean liberally with a brush, roller, lambswool applicator or broom. Let CUTEK® Quickclean do the work by leaving it on the surface for 5 to 15 minutes depending on the severity of dirt/soiling/grease. It may be necessary to scrub stubborn stains moderately with a soft bristle broom or stiff fibre brush.

Once CUTEK® Quickclean has cleaned the substrate, it must be rinsed off thoroughly. For best results, power rinse methodically with a high-pressure washer set to approximately 50 bar (750 p.s.i.) with a fan jet pattern.

CAUTION must be used when power rinsing to avoid damage to the wood fibre and 'furring up'. Adjust your cleaning process by reducing the pressure or adjusting your operating distance from the substrate to avoid damage.

Clean from the highest point and work down methodically using long even strokes in the direction of the grain. DO NOT use "turbojets" on timber. For situations where strong water washing is not practical, wash off with clean water from a bucket or a garden hose using a light scrubbing action with a stiff brush.

**Clean-up:** Equipment may be cleaned with water. Ensure wash water is disposed in accordance with local regulations



## IMPORTANT INFORMATION

CUTEK® Quickclean is a powerful general-purpose outdoor cleaner. It easily removes dirt, grease and grime and is the perfect way to clean your timber for a maintenance coat of CUTEK® wood oils.

It is important for the user to pre-determine the suitability of CUTEK® Quickclean for its intended application. ALWAYS do a test area prior to applying to any large sections. As surface types and conditions can vary significantly, pre-testing will enable you to accurately estimate the dilution, time and amount of CUTEK® Quickclean required to complete your project, and enable you to perfect the cleaning technique that works best in your situation.

CUTEK® Quickclean is a powerful general-purpose outdoor cleaner that should be diluted. Dilution can vary depending on the type of surface being cleaned and the build-up of dirt/grease on the substrate. Always pre-test prior to making a full mixture to determine if dilution being used is effective in cleaning on your specific surface.

NOTE: Not all stains can be removed with CUTEK® Quickclean. To rejuvenate grey, weathered timber or to remove stubborn stains such as iron stains, water marks, tannins, resins, mould and fungus etc. you will need to use CUTEK® Restore.

CUTEK® Quickclean will not remove film coatings.

## STORAGE & SAFETY

SAFETY	Read Data Sheet, SAFETY DATA SHEET and any precautions on container labels.
STORAGE	This product is NOT classified as dangerous goods for transport or storage in Australia. Store in well ventilated bunded area under cover and away from sources of heat. Keep containers closed at all times.
HANDLING	As with any chemical, ingestion, inhalation or contact with eyes and skin should be avoided by good occupational work practice. Eye protection approved to AS1337 and skin protection approved to AS2161 should be worn where there is a risk of splashes entering the eyes or contacting the skin. Always wash hands before smoking, eating, drinking or using the toilet.
USING	Use with good ventilation and avoid inhalation of spray mists and fumes. If risk of inhalation of spray mists exists, wear combined organic vapour/particulate respirator.
FLAMMABILITY	This product is not flammable. On burning may emit toxic fumes.



## COMPANY INFORMATION

Chemisys CUTEK® Pty Ltd

A.C.N. 610 127 654

130 Sandstone Place,

Parkinson QLD 4115

Australia

The data presented in this medium and any advice, recommendation, information, assistance or service provided by Chemisys in relation to goods manufactured by it or their use and application is given in good faith and is believed by Chemisys to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Chemisys does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from determining suitability of the product for their own purpose. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.